

07- 28 00

A

PATENT
Docket No. 5000-4777

Express Mail Label No. EK784975082US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

UTILITY APPLICATION AND APPLICATION FEE TRANSMITTAL (1.53(b))

Applicant(s) : Kotaro OAMI and Masaaki SUZUMURA
Serial No : TBA
Filed : July 27, 2000
For : INSERT FILM USED FOR FORMING RESIN PANEL, PROCESS FOR PRODUCING
THE FILM AND RESIN PANEL USING THE FILM

Box Patent Application - FEE
COMMISSIONER FOR PATENTS
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of

Named Inventor(s) and
Address(es): Kotaro OAMI and Masaaki SUZUMURA
of Kariya-shi, Aichi-ken, Japan;

For: INSERT FILM USED FOR FORMING RESIN PANEL, PROCESS FOR
PRODUCING THE FILM AND RESIN PANEL USING THE FILM

Enclosed are:

[X] 16 page(s) of specification, 1 page(s) of Abstract, 3 page(s) of claims


[X] 3 sheets of drawing [X] formal [] informal

[X] 4 page(s) of Declaration and Power of Attorney

[] Unsigned
[X] Newly Executed
[] Copy from prior application

[] Deletion of inventors including Signed Statement under 37 C.F.R. § 1.63(d)(2)

[] Incorporation by Reference: The entire disclosure of the prior application, from which a copy of the combined declaration and power of attorney is supplied herein, is considered as being part of the disclosure of the accompanying application and is incorporated herein by reference.



- ☐ Microfiche Computer Program (Appendix)
- ☐ _____ page(s) of Sequence Listing
- ☐ computer readable disk containing Sequence Listing
- ☐ Statement under 37 C.F.R. § 1.821(f) that computer and paper copies of the Sequence Listing are the same
- ☒ Claim for Priority (Claim to Convention Priority)
- ☒ Certified copy of the Priority Document
- ☐ English translation documents
- ☒ Information Disclosure Statement
- ☒ Copies of the cited references, including Form PTO-1449
- ☐ Copy of PTO-1449 filed in parent application serial No. _____.
- ☐ Preliminary Amendment
- ☒ Return receipt postcard (MPEP 503)
- ☒ Assignment Papers (assignment cover sheet and assignment documents)
- ☒ A check in the amount of \$40.00 for recording the Assignment.
- ☐ Assignment papers filed in parent application Serial No. _____.
- ☐ Certification of chain of title pursuant to 37 C.F.R. § 3.73(b).
- ☐ This is a ☐ continuation ☐ divisional ☐ continuation-in-part (C-I-P) of prior application serial no. _____.
- ☐ Cancel in this application original claims _____ of the parent application before calculating the filing fee. (At least one original independent claim must be retained for filing purposes.)
- ☐ A preliminary Amendment is enclosed. (Claims added by this Amendment have been properly numbered consecutively beginning with the number following the highest numbered original claim in the prior application.
- ☐ The status of the parent application is as follows:
- ☐ A Petition For Extension of Time and a Fee therefor has been or is being filed in the parent application to extend the term for action in the parent application until _____.
- ☐ A copy of the Petition for Extension of Time in the co-pending parent application is attached.
- ☐ No Petition For Extension of Time and Fee therefor are necessary in the co-pending parent application.

☐ Please abandon the parent application at a time while the parent application is pending or at a time when the petition for extension of time in that application is granted and while this application is pending has been granted a filing date, so as to make this application co-pending.

☐ Transfer the drawing(s) from the patent application to this application.

☐ Amend the specification by inserting before the first line the sentence:
This is a ☐ continuation ☐ divisional ☐ continuation-in-part of co-pending application Serial No. _____
_____ filed _____.

I. CALCULATION OF APPLICATION FEE (For Other Than A Small Entity)

	Number Filed		Number Extra	Rate	Basic Fee
Total					\$ 690.00
Claims	12	-20 =	--	x \$ 18.00	\$ --
Independent					
Claims	1	- 3 =	--	x \$ 78.00	\$ --
Multiple Dependent Claims					
	<input type="checkbox"/> yes		Additional Fee =	\$ 260.00	
	<input checked="" type="checkbox"/> no		Add'l Fee =	NONE	\$ 690.00

Total: \$ 690.00

☐ A statement claiming small entity status is attached or has been filed in the above-identified parent application and its benefit under 37 C.F.R. § 1.28(a) is hereby claimed. Reduced fees under 37 C.F.R. § 1.9(F) (50% of total) paid herewith \$ _____.

☒ A check in the amount of \$ 690.00 in payment of the application filing fees is attached.


☒ A check in the amount of \$ 40.00 in payment of the assignment recording fee is attached.

☐ Charge Fee(s) to Deposit Account No. 13-4500. Order No. _____. A DUPLICATE COPY OF THIS SHEET IS ATTACHED.

☒ The Assistant Commissioner is hereby authorized to charge any additional fees which may be required for filing this application, or credit any overpayment to Deposit Account No. 13-4500, Order No. 5000-4777. A DUPLICATE COPY OF THIS SHEET IS ATTACHED.

Respectfully submitted,

Dated: July 27, 2000


Alfred L. Haffner, Jr.
Registration No. 18,919

CORRESPONDENCE ADDRESS:

MORGAN & FINNEGAN, L.L.P.
345 Park Avenue
New York, New York 10154
(212) 758-4800
(212) 751-6849 Facsimile

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant(s) : Kotaro OAMI and Masaaki SUZUMURA
Serial No : TBA
Filed : July 27, 2000
For : INSERT FILM USED FOR FORMING RESIN PANEL, PROCESS FOR PRODUCING
THE FILM AND RESIN PANEL USING THE FILM

BOX: PATENT APPLICATION - FEE
Commissioner for Patents
Washington, D.C. 20231

EXPRESS MAIL CERTIFICATE

Express Mail Label No. EK784975082US
Date of Deposit July 27, 2000

I hereby certify that the following attached paper(s) and/or fee


New U.S. Patent Application for INSERT FILM FOR FORMING RESIN PANEL, PROCESS FOR PRODUCING
THE FILM AND RESIN PANEL USING THE FILM

- a. 16 pages of specification
- b. 1 page of Abstract
- c. 3 pages of claims
- d. 3 sheets of formal drawings (labeled)
- e. Application Fee Transmittal (in duplicate)
- f. Executed Declaration and Power of Attorney
1. Check for \$ 690.00 for filing fee
2. Check for \$ 40.00 for recording of Assignment
3. Executed Assignment together with Assignment Cover Sheet
4. Claim to Convention Priority
5. Certified Priority Document Application No.: 11-215541
6. Information Disclosure Statement
7. Form PTO-1449 with copies of the cited references
8. Return receipt postcard

is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37
C.F.R. §1.10 on the date indicated above and is addressed to the Commissioner for Patents, Box: Patent Application
- FEE, Washington, D.C. 20231.

Francisco J. Garcia

Typed or printed name of person
mailing paper(s) and/or fee)



(Signature of person mailing paper(s) and/or fee)

CORRESPONDENCE ADDRESS:
MORGAN & FINNEGAN, L.L.P.
345 Park Avenue
New York, New York 10154
(212) 758-4800
(212) 751-6849 Facsimile

INSERT FILM USED FOR FORMING RESIN PANEL, PROCESS FOR PRODUCING
THE FILM AND RESIN PANEL USING THE FILM

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to an insert film used for forming a resin panel, a process for producing the insert film and a resin panel using the insert film. More particularly, it relates to an insert film having provided therein a printed part.

Description of the Related Art

Conventionally, glass is used as a material for a window member of automobiles. However, glass has high specific gravity. Therefore, to attempt making the window material lightweight, a resin window using a resin such as polycarbonates or acrylic resins as a material thereof in place of glass is also used. For example, Japanese Patent Application Laid-Open No. 6-170883 discloses that, because a resin window has a softer surface as compared with a glass window, insert molding is conducted for integral molding by injecting a molten resin in a mold in a state such that a resin (polycarbonate) film or sheet in which one side has been subjected to a hard coat treatment is arranged in an injection molding mold with the hard coat side facing a mold wall, thereby a resin window having a hard coat layer formed on at least one side thereof.

Further, an opaque trimming part (blackout) for playing a role

of hiding a mounting portion of a body panel or a printed part for forming a sunshade or the like is sometimes arranged on a resin window. Fig. 6 is a perspective view of a resin window 32 provided with a trimming part as a printed part 31, and Fig. 7 is a partially sectional view thereof. As shown in Fig. 7, the printed part 31 is formed in a state so that it is sealed with a molding resin portion 33 and a resin film or sheet 34 (hereinafter referred to as "resin film 34" for simplicity). In Fig. 6, the printed part 31 is actually in a state that the entire part is completely coated with an ink of dark color, such as black.

In the case of producing such a resin window 32, the resin film 34 in which the printed part 31 is formed by an ink on the side opposite the side to which a hard coat treatment has been applied, is arranged in a fixed mold such that the printed part 31 faces a movable mold. After the movable mold is moved to close the mold, a molten resin is injected into the mold from a gate, thereby integrally molding with the resin film 34.

However, the ink has poor adhesiveness with a polycarbonate, which is a material of the resin film 34. Moreover, in order to attempt to not leave molding trace on an exposed surface of the resin window, if a gate for injecting a molten resin in a cavity of the mold is arranged at one edge side, the printed part 31 at the side near the gate receives great shear force from a molten resin of high temperature and high pressure. As a result, there

is the possibility that the surface of the printed part 31 is shaved off and flows away, or a part of the printed part 31 lifts from the resin film 34 and moves, and an ink flow 35 occurs as shown in Fig. 8 resulting in a defective product.

Further, there are the same problems, not limited to just the resin window, in the case where the desired pattern is formed on the surface of a resin panel by integrally molding an insert film or sheet having a printed part on the surface of a molten injection molded resin.

Japanese Patent Application Laid-Open No. 6-270188 discloses a method of solving this problem. That is, in a process for producing a molded product having a pattern thereon, by mounting a sheet having a character or pattern formed thereon on at least one side of a mold cavity such that the character- or pattern-processed surface faces the cavity side, and injecting a thermoplastic resin in the cavity, thereby integrally molding those, pressure and speed of a resin to be injected are controlled to prevent ink flow.

Further, Japanese Patent Application Laid-Open No. 7-308936 discloses that in producing a molded product having a pattern thereon by mounting a resin sheet or film (insert film) having formed thereon a pattern by a printing ink in a mold and injecting a molten thermoplastic resin in the mold, thereby integrally molding those, the sheet or film that the pattern formed by a printing ink is further

coated with a saturated thermoplastic polyester resin is used as the insert film, or a saturated thermoplastic polyester resin is contained in the printing ink.

However, in the case that the ink flow is prevented by controlling pressure and speed of the resin to be injected, as disclosed in Japanese Patent Application Laid-Open No. 6-270188, it is necessary to set proper conditions according to a shape and a size of a resin panel, and also there is the problem that a gate shape or a cavity depth of a mold is restrictive.

Further, adhesive force between a pattern and a molding material injected can be improved by covering a surface of a pattern (printed part) with a saturated thermoplastic polyester resin, or mixing a saturated thermoplastic polyester resin in a ink.

However, even if the surface of a pattern (printed part) is covered with a saturated thermoplastic polyester resin, adhesiveness between the ink and the insert film is poor. As a result, when receiving a large shear force in injecting a molding material, it is difficult to prevent ink flow due to lifting of a part of the printed part. Further, if a saturated thermoplastic polyester resin is contained in an ink, it results in diluting the ink. As a result, light transmission rate is not sufficiently suppressed by such a thickness obtained by a general printing method. On the other hand, if an amount of carbon or pigment in an ink is increased to thicken the ink, there is the problem that

inconveniences tend to occur in printing.

SUMMARY OF THE INVENTION

The present invention has been made to overcome the above-described problems.

A first object of the present invention is to provide a resin panel that can prevent an ink flow on a printed part when producing the resin panel or a generation of a gap between a printed part and a film or sheet with the passage of time after use, by a simple structure and at the same time without using a specific printing ink.

A second object of the present invention is to provide an insert film suitable for the production of a resin panel having a printed part therein.

The insert film according to the present invention is an insert film used to form a resin panel having a print that is arranged on a surface of a resin panel body, and comprises a resin film, a first binder layer formed on the surface of the resin film, a printed part formed on the first binder layer, and a second binder layer formed so as to seal the printed part in co-operation with the first binder layer.

A process for producing an insert film according to the present invention, is to produce the insert film described in claim 1. The process comprises a step of forming a first binder layer

on a surface of a resin film, a step of forming a printed part on the first binder layer, and a step of forming a second binder layer so as to seal the printed part in co-operation with the first binder layer.

The resin panel according to the present invention comprises the insert film as described in claim 1 and a resin panel body, the resin panel body being integrally molded with the insert film by insert molding in a state such that a surface of the resin film of the insert film at the side on which a printed part is formed faces inside.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view showing a resin window according to an embodiment of the present invention,

Fig. 2 is an enlarged sectional view taken along the line II-II in Fig. 1,

Fig. 3 is a partial sectional view of an insert film in a resin window according to an embodiment of the present invention,

Figs. 4A to 4C are partial sectional views showing a process for producing an insert film in order of steps,

Figs. 5A and 5B are partial sectional views of insert films according to modifications of the embodiment of the present invention,

Fig. 6 is a perspective view showing a conventional resin window,

Fig. 7 is a partial sectional view taken along the line VII-VII in Fig. 6, and

Fig. 8 is a plan view of a resin window illustrating a state where an ink flow occurs.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

One practical embodiment in which the present invention is embodied in a resin window of automobiles is hereinafter explained according to Figs. 1 to 4.

As shown in Figs. 1 and 2, a resin window 1 as a resin panel comprises a resin-made panel body 2 and an insert film 3 having the inside thereof a printed part 4 as a trimming part (blackout) formed along a periphery of the insert film 3, the insert film being integrally molded with the surface of the panel body by insert molding. The material of the panel body 2 is polycarbonate. In Fig. 1, the printed part 4 is actually the state that the entire surface thereof is completely coated with an ink of a dark color such as black.

As shown in Fig. 3, the insert film 3 comprises a resin film or sheet 5 (hereinafter referred to as "resin film 5" for simplicity), a first binder layer 6 applied to one side of the resin film 5, the printed part 4 formed on the first binder layer 6, and a second binder layer 7 formed so as to cover the printed part 4. The printed part 4 is sealed with the binder layers 6 and 7. A conventional

hard coat treatment is applied to a surface of the resin film 5 opposite the surface on which the printed part 4 is formed.

The first binder layer 6 is formed such that an area thereof is slightly larger than that of the printed part 4. Outer periphery 6a of the first binder layer 6 does not coincide with a periphery 5a of the resin film 5, so that there remains an area 8 where a surface of the resin film 5 is exposed. The second binder layer 7 is formed such that its periphery 7a coincides with the periphery 6a of the first binder layer 6. Each of the binder layers 6 and 7 is set to have a thickness of 2 to 30 μm , and the printed part 4 is set to have a thickness of 2 to 30 μm .

As the resin film 5, for example, a polycarbonate film having a thickness of 0.1 to 1.0 mm is used. The material for each of the binder layers 6 and 7 used is a vinyl chloride-vinyl acetate copolymer. The vinyl chloride-vinyl acetate copolymer is applied in a state of being dissolved in a solvent. Ink for the printed part 4 is one comprising, for example, a polyester resin as a main component, and a dye or pigment having the desired color, dissolved or dispersed in a solvent. An acrylic resin, vinyl chloride resin, urethane resin or the like may be used in place of the polyester resin.

A process for producing the resin window 1 is explained below. First of all, a process for producing the insert film 3 is explained according to Figs. 4A to 4C.

The insert film 3 is formed by successively printing the first binder layer 6, the printed part 4 and the second binder layer 7 on one surface of the resin film 5, on the other surface of which having been subjected to a hard coat treatment, by a screen printing or the like. The resin film 5 to which a hard coat treatment has been subjected is set to a screen printing machine such that the surface opposite the hard coat treated surface faces the screen, and the first binder layer 6 is printed on the predetermined position as shown in Fig. 4A. The first binder layer 6 is formed in a state such that the area 8 is formed between an outer periphery 6a of the first binder layer 6 and a periphery 5a of the resin film 5. After the first binder layer 6 has dried, the printed part 4 is printed on the first binder layer 6 as shown in Fig. 4B. The printed part 4 is set such that a distance L between the edge thereof and the edge of the first binder layer 6 is at least 0.2 mm. After an ink has dried, the second binder layer 7 is printed so as to cover the printed part 4. The second binder layer 7 is printed in a state such that the periphery 7a thereof overlaps with the periphery 6a of the first binder layer 6 as shown in Fig. 4C. When the second binder layer 7 has dried, the production of the insert film 3 is completed.

The insert film 3 is then fixed on the predetermined position in a fixed mold of an injection molding mold, such that the surface having the printed part 4 formed thereon faces a movable mold. After

closing the movable mold, a molten resin (polycarbonate) is injected in a cavity from a gate. The injected polycarbonate fills the cavity in a state of covering the surface of the printed part 4 side of the insert film 3 set in the mold, and the insert film 3 is integrally molded on the surface of the panel body 2 as shown in Fig. 1. After cooling the mold, a molded product is taken out of the mold. Burrs are removed and the resin window 1 is completed.

In conducting the insert molding, the gate for injecting the molten resin in the cavity of the mold is arranged at one edge side of the molded product. Therefore, the vicinity of the printed part 4 near the gate receives a large shear force from the molten resin that has high temperature and high pressure. Because the cavity side of the printed part 4 is covered with the second binder layer 7, the molten resin is not directly in contact with the printed part 4, and the printed part 4 is suppressed to receive a large shear force. As a result, the surface of the printed part 4 is not shaven, and an ink flow due to an ink shaving is prevented. However, since the printed part 4 is arranged with a wide solid coating along the periphery of the insert film 3. However, the width of the part of the second binder layer 7 which is directly adhered to the first layer 6 outside of the printed part 4 is narrow.

Thus, if the first binder layer 6 is not present as in the conventional technique, when the second binder layer 7 receives a large shear force from the molten resin during an injection molding,

there is the possibility that a part of the second binder 7 peels off, an ink having a poor adhesiveness with the resin film 5 lifts from the resin film 5, and an ink flow occurs. However, according to the present invention, because the first binder layer 6 is present between the printed part 4 and the resin film 5, and also the printed part 4 is sealed with the first and second binder layers 6 and 7, the printed part 4 is prevented from lifting from the resin film 5 and, as a result an ink flow is surely prevented.

Due to the area 8 being formed between the peripheries 6a and 7a of the first binder layer 6 and the second binder layer 7 and the periphery of the resin film 5, the peripheral portion of the resin film 5 is integrally molded with the panel body 2 in a direct contact state through the area 8. The adhesiveness between the resin film 5 and the panel body 2 is superior than the adhesiveness between the first binder layer 6 and the resin film 5 or between the second binder layer 7 and the panel body 2. Therefore, as compared with the case that the peripheral portion of the resin film 5 is integrally molded with the panel body 2 through the first and second binder layers 6 and 7, the peripheral portion of the resin film 5 is maintained in a state of closely adhering to the panel body 2.

The resin window 1 constituted as above is used when mounted to a window of automobiles. The resin window 1 is adhered to a car body panel with an adhesive, and the printed part 4 plays a role

of hiding a fixed portion of the resin window 1, and shielding the adhesive from sunlight, thereby suppressing deterioration of the adhesive. In the case that the first binder layer 6 is not present, even if a molding is successfully conducted, a gap tends to generate between the printed part 4 and the resin film 5 with the passage of time during use. However, due to the presence of the first binder layer 6, adhesiveness of the printed part 4 to the resin film 5 is improved and this prevents formation of a gap between the printed part 4 and the resin film 5 with the passage of time.

This embodiment has the following effects.

(1) The printed part 4 is printed on the first binder layer 6 formed on the resin film 5, and also sealed with the first binder layer 6 and the second binder layer 7 formed on the printed part 4. Therefore, when the insert film 3 is arranged in a mold and a molten resin is injected in the mold, a good adhesiveness between the printed part 4 and the resin film 5 is secured by the first binder layer 6, and the printed part 4 is protected by the second binder 7. As a result, an ink flow is prevented from occurring. Further, due to the presence of the first binder layer 6, a gap can be prevented from being generated between the printed part 4 and the resin film 5 with the passage of time after the completion of a molded product.

(2) The printed part 4 is formed as a trimming portion along the peripheral portion of the resin film 5. Because the area 8 is

formed between the peripheries 6a and 7a of the first binder layer 6 and the second binder layer 7 and the periphery 5a of the resin film 5, the peripheral portion of the resin film 5 is integrally molded with the panel body 2 in a state of being directly in contact with the panel body 2. Therefore, due to the presence of the printed part 4 formed as a trimming portion along the peripheral portion of the resin film 5, the peripheral portion of the insert film 3 that is liable to peel off the panel body 2 is maintained in a state of closely adhering to the panel body 2.

(3) The panel body 2 and the resin film 5 are both made of the same material, and the first binder layer 6 and the second binder layer 7 are made of the same material. Therefore, as compared with the case that the panel body 2 and the resin film 5 are made of different material, the adhesiveness at the interface thereof is improved, and by using the binder layers made of the same material a good adhesiveness of the printed part 4 to the panel body 2 and the resin film 5 can be secured.

(4) Polycarbonate is used as a material of the panel body 2 and the resin film 5. Therefore, a material conventionally used as a resin window of automobiles can be used as it is, and function that is necessary as the resin window 1 can be secured.

(5) The insert film 3 can easily be produced by successively forming the first binder layer 6, the printed part 4 and the second binder layer 7 on the predetermined position of the resin film 5.

(6) The printed part 4 and the two binder layers 6 and 7 are formed on the resin film 5 by a screen printing. Therefore, the printed part 4 and the two binder layers 6 and 7 can be formed on the predetermined position of the resin film 5 with good accuracy.

The embodiment is not limited to the above one, and for example, the following modifications and changes can be made.

The two binder layers 6 and 7 are not limited to the structure of being formed in a state such that those peripheries coincide, but it is sufficient if only the printed part 4 is sealed with both two binder layers 6 and 7. For example, the two binder layers 6 and 7 may be formed by laminating such that the periphery 17a of the second binder layer 17 is located inside the periphery 6a of the first binder layer 6 as shown in Fig. 5A, or by completely covering the first binder layer 6 with the second binder layer 27 so that the peripheral portion 27a of the second binder 27 closely adheres to the resin film 5.

The two binder layers 6 and 7 may be formed such that the outer periphery of at least one of the binder layers coincides with the periphery of the resin film 5. In other words, an area may not be present between the peripheries of the binder layers and the periphery of the resin film 5.

The first binder layer 6 and the second binder layer 7 need not always be made of the same material. The two binder layers may be made of different material if the first binder layer 6 has a

good adhesiveness with the printed part 4 and the resin film 5, and the second binder layer has a good adhesiveness with the printed part 4 and the panel body 2. However, since the same material is generally used for the panel body 2 and the resin film 5, the use of the same material for the two binder layers 6 and 7 makes it easy to secure a good adhesiveness at the interface of the two binder layers 6 and 7, and a good adhesiveness of each binder layer with the panel body 2 or the resin film 5.

The printed part 4 is not limited to a blackout formed at the peripheral portion of the resin window 1, but a pattern as a sunshade, a conductive linear pattern such as anti-fogging and ice-melting heat wires or antennas for a car radio or a decorative pattern may be provided.

The printed part 4 and both binder layers 6 and 7 may be formed by a method other than a screen printing.

The resin window 1 is not limited to use for automobiles, but may be applied to a resin window for windows of buildings, or a resin panel such as for partitioning or decorative panel and the like.

In the case that the resin window is applied to a resin panel other than the resin window 1 for automobiles, a blackout may be omitted as the printed part 4.

The resin film 5 used in the above embodiments does not limit its thickness, and generally includes a sheet than is considered

to be thicker than a film.

In the case that the resin panel is applied to a resin window for automobiles, it is not limited to the structure in which the resin panel is directly secured to a car body panel. Instead, the resin panel may be secured to the car body panel through the intermediary of a frame for reinforcement. In the case that the resin panel is secured to the frame with an adhesive, a blackout should be positioned so as to hide the adhered portion.

WHAT IS CLAIMED IS:

1. An insert film used to form a resin panel having a print therein by arranging the film on a surface of a resin panel body, said insert film comprising:

a resin film;

a first binder layer formed on the surface of the resin film;

a printed part formed on the first binder layer; and

a second binder layer formed so as to seal said printed part in co-operation with the first binder layer.

2. The insert film according to claim 1, wherein a surface of said resin film is exposed on the outside of a periphery of the first binder layer.

3. The insert film according to claim 1, wherein said second binder layer covers the periphery of said first binder layer to directly adhere closely to the resin film, a surface of said resin film being exposed on the outside of a periphery of the second binder layer.

4. The insert film according to claim 1, wherein a material of the first binder layer is the same as that of the second binder layer.

5. A process for producing the insert film of claim 1 comprising:

a step of forming a first binder layer on a surface of a resin film;

a step of forming a printed part on the first binder layer;
and

a step of forming a second binder layer so as to seal said printed part in co-operation with the first binder layer.

6. The process for producing the insert film according to claim 5, wherein the first and second binder layers and the printed part are formed by a screen printing.

7. A resin panel comprising:

the insert film of claim 1; and

a resin panel body integrally molded with the insert film by an insert molding in a state such that a surface of the resin film of the insert film at the side on which a printed part is formed faces inside.

8. The resin panel according to claim 7, wherein said resin panel body is directly adhered closely to said resin film at an outer side of the periphery of the first binder layer.

9. The resin panel according to claim 7, wherein said second binder layer covers the periphery of the first binder layer to directly adhere closely to said resin film and said resin panel body directly adheres closely to said resin film on an outer side of the periphery of said second binder layer.

10. The resin panel according to claim 7, wherein said resin panel is a window for automobiles.

11. The resin panel according to claim 7, wherein a material

of said resin panel body is the same as that of said resin film.

12. The resin panel according to claim 11, wherein a material of said resin panel body and said resin film is polycarbonate.

ABSTRACT OF THE DISCLOSURE

An insert film having a printed part is integrally molded to a surface of a panel body made of a resin by an insert molding. The printed part is printed on a first binder layer applied to a resin film and also is formed on the resin film in a state such of being sealed with the first binder layer and a second binder layer applied on the printed part. The printed part is formed as a trimming portion (blackout) along a peripheral portion of the resin film, and an area is formed between the peripheries of the first binder layer and the second binder layer and the periphery of the resin film.

FIG. 1




FIG. 2





FIG. 3






FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7





FIG. 8



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

INSERT FILM USED FOR FORMING RESIN
 PANEL, PROCESS FOR PRODUCING THE
 FILM AND RESIN PANEL USING THE FILM

上記発明の明細書（下記の欄でx印がついていない場合は、本表に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約
 国際出願番号を _____ とし、
 （該当する場合） _____ に訂正されました。

☐ was filed on _____
 as United States Application Number or
 PCT International Application Number
 _____ and was amended on
 _____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定議されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner of Patents and Trademarks, Washington, DC 20231.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づき国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)

外国での先行出願

11-215541	Japan
(Number)	(Country)
(番号)	(国名)
_____	_____
(Number)	(Country)
(番号)	(国名)

私に、第35編米国法典119条(e)項に基づいて下記の米国外の特許出願規定に記載された権利をここに主張いたします。

_____	_____
(Application No.)	(Filing Date)
(出願番号)	(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国外の特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国外の特許出願に開示されていない限り、その先行米国外出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

_____	_____
(Application No.)	(Filing Date)
(出願番号)	(出願日)
_____	_____
(Application No.)	(Filing Date)
(出願番号)	(出願日)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の表明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

29 / 07 / 1999
(Day/Month/Year Filed)
(出願年月日)

(Day/Month/Year Filed)
(出願年月日)

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

_____	_____
(Application No.)	(Filing Date)
(出願番号)	(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration
(日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁理士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

I hereby appoint John A. Diaz (Reg. No. 19,550), John C. Vassil (Reg. No. 19,098), Alfred P. Ewert (Reg. No. 19,887), David H. Pfeffer, P.C. (Reg. No. 19,825), Harry C. Marcus (Reg. No. 22,390), Robert E. Paulson (Reg. No. 21,046), Stephen R. Smith (Reg. No. 22,615), Kurt E. Richter (Reg. No. 24,052), J. Robert Dailey (Reg. No. 27,434), Eugene Moroz (Reg. No. 25,237), John F. Sweeney (Reg. No. 27,471), Arnold I. Rady (Reg. No. 26,601), Christopher A. Hughes (Reg. No. 26,914), William S. Feiler (Reg. No. 26,728), Joseph A. Calvaruso (Reg. No. 28,287), James W. Gould (Reg. No. 28,859), Richard C. Komson (Reg. No. 27,913), Israel Blum (Reg. No. 26,710), Bartholomew Verdirame (Reg. No. 28,483), Maria C.H. Lin (reg. No. 29,323), Joseph A. DeGirolamo (Reg. No. 28,595), Michael A. Nicodema (Reg. No. 33,199), Michael P. Dougherty (Reg. No. 32,730), Seth J. Atlas (Reg. No. 32,454), Andrew M. Riddles (Reg. No. 31,657), Bruce D. DeRenzi (Reg. No. 33,676), Michael M. Murray (Reg. No. 32,537), Mark J. Abate (Reg. No. 32,527), Alfred L. Haffner, Jr. (Reg. No. 18,919), Harold Haidt (Reg. No. 17509) and Steven F. Meyer (Reg. No. 35613), each of whom is a member of the Bar of the State of New York, and Edward A. Pennington (Reg. No. 32,588), a member of the Bar of the State of Virginia, and each of them, as my attorney with full power of substitution and revocation, to prosecute this application, receive the patent and to transact all business in the Patent and Trademark Office connected therewith.

書類送付先

Send Correspondence to:

Alfred L. Haffner, Jr.
Morgan & Finnegan, L.L.P.
345 Park Avenue
New York, NY 10154

直接電話連絡先： (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

Alfred L. Haffner, Jr.
Telephone: (212) 415-8700
Facsimile: (212) 751-6849

唯一または第一発明者名	Full name of sole or first inventor Kotaro OAMI		
発明者の署名	日付	Inventor's signature <i>Kotaro Oami</i>	Date <i>July 20, 2000</i>
住所	Residence Aichi-ken, Japan		
国籍	Citizenship Japan		
私書箱	Post Office Address c/o Kabushiki Kaisha Toyoda Jidoshokki Seisakusho, 2-1, Toyoda-cho, Kariya-shi, Aichi-ken, Japan		

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for second and subsequent joint inventors.)

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

第二共同発明者		Full name of second joint inventor, if any Masaaki SUZUMURA	
第二共同発明者	日付	Second inventor's signature Masaaki Suzumura	Date July 20, 2000
住所		Residence Aichi-ken, Japan	
国籍		Citizenship Japan	
私書箱		Post Office Address c/o Kabushiki Kaisha Toyoda Jidoshokki Seisakusho, 2-1, Toyoda-cho, Kariya-shi, Aichi-ken, Japan	
第三共同発明者		Full name of third joint inventor, if any	
第三共同発明者	日付	Second inventor's signature	Date
住所		Residence	
国籍		Citizenship	
私書箱		Post Office Address	
第四共同発明者		Full name of fourth joint inventor, if any	
第四共同発明者	日付	Second inventor's signature	Date
住所		Residence	
国籍		Citizenship	
私書箱		Post Office Address	

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for fifth and subsequent joint inventors.)